



Technical Data Sheet

ISO FIT ISOHULK ALUMINIUM Tape

ISO FIT ISOHULK38CWR Tape

DESCRIPTION

A 30 micron aluminum tape with a special flame retardant adhesive. The ISO FIT ISOHULK 38CWR adhesive tape, has an aggressively high tack and good long-lasting adhesive properties. It has excellent temperature and high aging resistance.

APPLICATIONS

Thermal insulation

Sealing

Moisture and steam protection

Shipbuilding, HVAC systems and refrigeration construction Carrier

ADHESIVE

30 micron aluminum foil

Solvent free acrylic adhesive, very low in halogen & formaldehyde

Adhesive-repellent paper liner, pe-liner or kraft liner Technical

TECHNICAL DETAILS

CHARACTERISTICS	VALUE	TESTMETHODE
Thickness	70 micron	PSTC-133
Adhesion to Steel	30 micron	PSTC-133
Tensile Strength	60 N/25mm	PSTC-131
Temperature Resistance	-40 °C/ +120 °C	–
Applying temperature	+10 °C	–
Flame Retardancy	Class 0 – Class 1Passed B1	UL 723 & BS476 DIN 4102
IMO Med Certifications	IMO SOLASMODULE B & D	–

STORAGE

Clean and dry in a well-ventilated room, preferably at a temperature between 15°C and 25°C.

Disclaimer : The above information is given in good faith, but the user should insure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

Tape Solutions cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.